



40,000 CFM TRAILER DIESEL POWERED DUST COLLECTOR

FEATURES

▶ FILTRATION

- ▶ 40,000 CFM at 12" WC
- ▶ 15,600 sq. ft. moisture resistant cellulose resin material
- ▶ 2.56:1 air to cloth ratio
- ▶ 60 Top loading cartridges

▶ FILTER CLEANING: Timed cycle reverse air pulse

▶ FILTER EFFICIENCY: 99.8% at .5 micron particle

▶ AIR INLETS: (6) 20" diameter, 2 per side and 2 rear

▶ MATERIAL DISCHARGE: Hydraulic powered auger

▶ FAN: Non-overloading, spark resisting

▶ FUEL: 120 gallons, consuming 7.5 gallons per hour

▶ ELECTRICAL SYSTEM: 12V dc

▶ BREAKS: Electric

▶ WARRANTY: One Year Limited

OPTIONS

▶ Diesel Powered: Liquid Cooled Tier 3 178 HP

▶ Electric Powered: 150 HP 480 VAC 3 PH

▶ Filters:

- ▶ Standard Qx Media 80/20 Blend
- ▶ SB (Spun Bonded Polyester)
- ▶ HEPA Secondary Final Filter
- ▶ Filter Restriction Warning Light

▶ Pulse System: On board Air Compressor

▶ Waste Removal:

- ▶ Hydraulic Powered Auger
- ▶ Vibrator - Air Powered
- ▶ Vibrator - Electric Powered

▶ Hopper Configuration: Quick release inlet connectors and clamps

▶ Jack: Heavy Duty Jack

▶ Frame Configuration:

- ▶ Skid With Auger Discharge
- ▶ Trailer With Auger Discharge
- ▶ Crane Pick Points
- ▶ Fork Lift Pockets

▶ Storage:

- ▶ Storage Boxes
- ▶ Under Hopper Storage Boxes

▶ Fuel:

- ▶ Large Fuel Fill
- ▶ Grease Gun
- ▶ Tie Down Points

▶ Dryer: Air Dryer

▶ Paint: Custom Company Color



384"

132"

WEIGHT: 20,000 lbs

WIDTH: 96"