



MS-17,500 | 15,000-ARID-DRY UNITS DEHUMIDIFIER

FEATURES / SPECIFICATIONS

- ▶ Max Air Volume - 17,5 CFM
- ▶ Electric, LP or natural gas
- ▶ Skid mounted with lifting cage
- ▶ Desiccant wheel and heater banks
- ▶ Available Accessories:
 - ▶ Available Accessories
 - ▶ Remote Humidista
 - ▶ Cooling Coil Modules
 - ▶ Heating Coil Modules
 - ▶ Trailer Mounting with generators
 - ▶ (3) 18" or 20" Round Connections

WEIGHT: 10,650 lbs | WIDTH: 88"

108"



221"

MaxAir Volume	Moisture Removal Lbs/Hr 80°/60% RH	Moisture Removal Gallons/Day 80°/60% RH	Moisture Removal Lbs/Hr 55°/80% RH	Moisture Removal Gallons/Day 55°/80% RH	Moisture Removal Lbs/Hr 40°/80% RH	Moisture Removal Gallons/Day 40°/80% RH
17,500	442	1,272	368	1,061	252	728

Pipe Size	LP Inlet Pressure	Natural Gas Inlet Pressure	Electric Reactivation Load 230/1/60	Electric Reactivation FLA Load 460/3/60	Gas Reactivation FLA Load 460/3/60	CFH Gas Max Usage NG	Gallon/HR Max Usage LP
1½"	7-14" w.c.	7-14" w.c.	N/A	335	44	1,200	12.7