



DH5000 DESICCANT DEHUMIDIFIER

FEATURES / SPECIFICATIONS

- ▶ Max Air Volume - 6,000 CFM
- ▶ External Static Pressure - 2.0
- ▶ Electric, LP or natural gas
- ▶ Skid mounted with lifting cage
- ▶ Desiccant wheel and heater banks
- ▶ Available Accessories:
 - ▶ Remote Humidistat
 - ▶ Cooling Coil Modules
 - ▶ Heating Coil Modules
 - ▶ Trailer Mounting with generators
 - ▶ 5.0 Static Pressure External
 - ▶ 18" or 20" Round Connections
 - ▶ Protective Cage

WEIGHT: 5,400 lbs | WIDTH: 48"

66"



168"

Model	Static Pressure External	Moisture Removal Lbs/Hr	Moisture Removal Gallons/Day	Moisture Removal Lbs/Hr	Moisture Removal Gallons/Day	Moisture Removal Lbs/Hr	Moisture Removal Gallons/Day
		80%/60% RH	80%/60% RH	55%/80% RH	55%/80% RH	40%/80% RH	40%/80% RH
CDH-138	2.0	136	392	115	331	75	216

Model	Air Volume	Electric Reactivation Load	Electric Reactivation FLA Load	Gas Reactivation FLA Load	CFH Gas Max Usage	Gallon/HR Max Usage
		220/1/60	460/3/60	460/3/60	LP	LP
CDH-138	5,000	N/A	138	13	400	4.4