

# HURRICANE 755 DIESEL POWERED VACUUM

# FEATURES

### ► TRAILER MOUNTED

- Chassis tandem 8,000# axles, 4"x 6" rectangular tube frame, with four 8-lug P225/R-16 ten ply, steel beltedradials. DOT lighting with electric brakes. Trailer light wiring harness, with 7-pin connector.
- POWER SOURCE: John Deere Tier 4 turbo-charged diesel, 6.8 liter, 225 HP@ 2,200 RPM
- ▶ P.T.O. (clutch): Double disc, 11.5" with iron plates
- VACUUM AIR FLOW (Blower)
  - Roots Dresser 3660 CFM capable of 28" Hg, direct drive through flex coupling, w/ easy access guard
- FILTRATION SYSTEM (3-Stage)
  - ► Stage 1: Cyclonic separation
  - ▶ Stage 2: Baghouse/37 Teflon coated, quick change

## STANDARD EQUIPMENT

Paint - one color, wet or dry operation, automatic cone vibrator, 100 gal fuel tank, & hydraulic lift leg to level trailer, spare tire & carrier, tool box, adjustable pintle hook, emergency stop button, dual front hydraulic lift legs to level trailer, spare tire & carrier, & hinged dome on baghouse

# **OPTIONS & SAFETY FEATURES**

- Cold weather package, optional HEPA filtration, slide gate discharge, Hazardous waste package, auger in cone, auxiliary air hose 120 PSI, skid mount, 200 HP electric motor, 4 point certified lifting cage, high reach package, gooseneck trailer, high reach package for discharge up to 11 ft
- OSHA approved drive guard, emergency stop button & trailer breakaway chain, safety struts for baghouse, wheel chocks, optional HEPA filtration, electric brakes, & low oil or high temp engine shutdown

bags w/ continuous reverse pulse air cleaning

- Stage 3: Dual high efficiency blower safety filters with dirty filter shut-down system
- ► HYDRAULICS: 4.5 GPM, 2200 PSI, direct drive
- ► ENCLOSURE: Lockable steel shroud over major parts
- INSTRUMENT PANEL (fully enclosed)
  - ► 12V key start, safety system, Digital: oil pressure, water temp, ammeter, RPM, hour meter. Filter cleaning on/off switch, material vacuum & dump time controls, air compressor psi gauge
- ► AIR COMPRESSOR
  - Direct drive Bendix twin cylinder; water cooled & oil pressure fed. Haldex air dryer with electronic heater. AMSE certified air tank mounted on vibration isolator

### WEIGHT: 13,500 LBS WIDTH: 99"

Hitch to ground 29.5" 89" High reach option up to 11' discharge height



888.281.2643

Nationwide Availability

www.MES.us