



HURRICANE 800

ELECTRIC POWERED VACUUM

FEATURES

▶ SKID MOUNTED

- ▶ 4" X 8" rectangular tube frame, 6"x 12" fork pockets. 4 point certified lift frame. Sub frame for motor & blower package with vibration isolators.

▶ POWER PACKAGE 1

- ▶ 200 HP electric motor, 460 volt, 3-phase hostile duty motor. Direct drive to a Roots 4500CFM blower capable of 28"of mercury (Hg)

▶ POWER PACKAGE 2

- ▶ 300 HP electric motor, 460 volt, 3-phase hostile duty motor. Direct drive to a Roots 5660CFM blower capable of 28"of mercury (Hg)

▶ FILTRATION SYSTEM (3-Stage)

- ▶ Stage 1: Cyclonic separation
- ▶ Stage 2: 37 Teflon coated, quick change bags w/ continuous reverse pulse air cleaning
- ▶ Stage 3: Dual blower safety filters w/ optional HEPA filtration

▶ INSTRUMENT PANEL

- ▶ Soft start package, push button motor on/off w/ indicator light, disconnect lever, filter cleaning on/off, vacuum system on/off

STANDARD EQUIPMENT

- ▶ Paint one color with custom lettering/stripping
- ▶ Wet or dry operation
- ▶ Automatic cone vibrator
- ▶ Emergency stop button
- ▶ 10" inspection manhole

OPTIONS & SAFETY FEATURES

- ▶ HEPA filtration
- ▶ Dirty filter shut down system
- ▶ Slide gate discharge
- ▶ Toolbox
- ▶ Hydraulic lift package
- ▶ Air compressor -120PSI
- ▶ Trailer mounted
- ▶ Hydraulic auger in cone
- ▶ Rotary valve
- ▶ Double dump valve

WEIGHT: 12,500 LBS | WIDTH: 88"

